

Door alarms: Advanced and multi-purpose



PG21MS Series surface-mount narrow stile door alarms. Ideal in schools, nursing homes, restaurants & theatres

Models PG21MS/PG21MB

- Two selectable arming modes –
 1. **Always armed mode** – when key is turned counter clockwise to the disarm position, the key cannot be removed. To remove key, turn back to arm mode, thus keeping unit armed always.
 2. **Standard arming mode** – when key is inserted turning counter clockwise will disarm and key can be removed. Turning key clockwise will arm and key can be removed.
- Improve security at any door, and stop door-propping vulnerability
- Sweeping 95db alarm &/or strobe
- “Always Armed” when key is removed or Standard Arming modes
- Narrow Stile, advanced microprocessor control
- Easy installation
- Relay option
- Tamper supervised
- Entry Delay Options: 15 seconds; 1 min. 15 sec.; 3 mins 15 sec.
- Unauthorized use of door causes alarm to sound and activates LED indicator &/or optional strobe on MSS/MBS models (shown left)
- Choose continuous alarm, minute shutdown with auto reset and exit/entry delay
- Tamper switch supervised
- For exterior key control, optional RIM cylinder may be used
- Metallic silver or duronodic finish. Red Armed Status Indicator.
- Relay option. Option for continuous power with external power supply added.
- Uses standard mortise cylinder (not included)



Multiple door monitoring with built-in external reed switches, too.

Model PG30KPD:

Keypad-controlled narrow stile door alarm, similar to PG21, plus:

- Digital codes for master, management and passage (used for auto-arming)
- 3 security levels for: a) high security b) unattended applications c) flexible control for delivery doors, etc.
- Audible low battery warning
- 3 Programmable 95db siren styles: sweep, pulsed, and steady
- Logo key is dual function test button



PG30KPD Accessory:

- For optional use with the PG30, this low-profile, brushed aluminum finished accessory provides all functions of the PG30 from the outside of the door. (Available in metallic silver only.)

Model PG10

- The Pilfergard Model PG10 is an exit door alarm designed to deter the use of the secured door by sounding a twin action alarm when opened by unauthorized personnel. The alarm can be bypassed from inside or outside by the use of a key. (Requires standard mortise cylinder not supplied.) This durable surface mount unit is easily installed and is tamper-supervised with two separate tamper switches. Its test button verifies battery. Optional AC power supply available.



Model LL1

- All of the features of the PG10 unit with addition of a flashing strobe for easy alarm identification.
- Choice of system controllers

