

# CORBIN RUSSWIN

## Mortise Locks

### ML2000 Series

#### Features

- Handing: Handed; quick reversible. The lockset can be re-handled without disassembling the lock case.
- Door Thickness: 1-3/4" standard. Optional door thickness available.
- Backset: 2-3/4".
- Front: Heavy gauge steel, 8" x 1-1/4" x 3/32". Accommodates flat doors and doors beveled 1/8" in 2". Optionally furnished 1-1/16" wide for 1-3/8" doors.
- Armored Front: Wrought brass or bronze, attached by machine screws to lockcase front.



- Latchbolt: 2-piece mechanical with anti-friction insert, 5/8" x 1" x 3/4" throw.
- Auxiliary Latchbolt: 9/16" effective throw and 3/8" effective auxiliary latch deadlocking.
- Deadbolt: One-piece stainless steel, 19/32" x 1-1/4" x 1" throw.
- Strike: Wrought brass or bronze, ANSI straight lip standard, 4-7/8" x 1-1/4" x 1-1/8" lip to center. Optional strikes, lip lengths and ANSI wrought strike box available.
- Cylinder: Brass, 6-pin, L4 keyway. Other keyways available.
- Keys: Two nickel silver standard.
- Finishes: 626/630 and other standard architectural finishes.

#### Certification/Compliance

ANSI: Meets A156.13 Series 1000, Operational and Security Grade 1. Meets A117.1 Accessibility Code.

#### Functions

OUTSIDE	INSIDE	SERIES/ FUNCTION	TYPE	ANSI NO. SERIES 1000	FUNCTION DESCRIPTION
		ML2010	Passage or Closet	F01	Latchbolt by grip either side. Both grips always free.
		ML2020	Privacy Bedroom or Bathroom	F02	Latchbolt by grip either side. Deadbolt by thumbturn lever inside or by emergency release tool outside.
		ML2051	Entrance or Office	F04	Latchbolt by key outside or by grip either side, unless outside grip is locked by toggle-action stop. Auxiliary latch deadlocks latchbolt. Inside grip always free.
		ML2055	Classroom	F05	Latchbolt by grip either side, unless outside grip is locked by key outside. Auxiliary latch deadlocks latchbolt. Inside grip always free.
		ML2057	Storeroom or Closet	F07	Latchbolt by grip inside or by key outside. Outside grip always rigid. Auxiliary latch deadlocks latchbolt. Inside grip always free.


Note: Corbin Russwin manufactures locks in a wide variety of functions to meet commercial, residential and institutional requirements. Not all functions are shown in this catalog. If your requirements are not met by what is shown here, please contact us.

Indicates lever rigid at all times.

**Trim Designs for ML2000**


**IWA**

Lever: Wrought  
Rose: Wrought  
Door thickness:  
1-3/8", 1-3/4", 2-1/4"




**NSA**

Lever: Cast  
Rose: Wrought  
Door thickness:  
1-3/8", 1-3/4", 2-1/4"




**LWM**

Lever: Wrought  
Escutcheon: Wrought  
Optional: Plug only to show; master ring  
Door thickness:  
1-3/8", 1-3/4", 2-1/4"



**CSA**

Lever: Cast  
Rose: Wrought  
Door thickness:  
1-3/8", 1-3/4", 2-1/4"



*Note: Trim designs shown are only a small sample of the wide variety available. If your needs are not met by what is shown here, please contact us.*

**CL3300 Series Extra Heavy Duty Cylindrical Lever Locksets**

**Features**

- Lever handle is free-wheeling in locked position.
- Handing: Non-Handed.
- Door Thickness: 1-3/4" to 2" standard. Optional: 2" to 2-1/4".
- Backset: 2-3/4" standard. Optional: 3-3/4" and 5".
- Front: 2-1/4" x 1-1/8". Accommodates flat doors and doors beveled 1/8" in 2".
- Latchbolt: 1/2" throw. Optional: 3/4" throw deadlocking fire latch for pair of doors.
- Auxiliary Latchbolt: Deadlocking latchbolt prevents manipulation when door is closed.
- Strike: ANSI curved lip standard, 4-7/8" x 1-1/4" x 1-1/4" lip to center. Optional strikes, lip lengths and ANSI wrought strike box available.
- Cylinder: Brass, 6-pin L4 keyway. Other keyways available.
- Keys: Two nickel silver standard.
- Finishes: Available in 626 and other standard architectural finishes.



**Certification/Compliance**

ANSI: Meets A156.2 Series 4000, Grade 1. Meets A117.1 Accessibility Code.

**CL3600 Series**

**Features**

- Lever handle is free-wheeling in locked position.
- Handing: Non-handed (except for CL3629, CL3680, CL3681, CL3690, CL3691; specify hand).
- Door Thickness: 1-3/8" to 2" standard. Optional: 2-3/8", 3-3/4", and 5".
- Front: 2-1/4" x 1-1/8" for 2-3/4" backset; 2-1/4" x 1" for 2-3/8" backset. Accommodates flat doors and doors beveled 1/8" in 2".
- Latchbolt: 1/2" throw.
- Auxiliary Latchbolt: Deadlocking latchbolt prevents manipulation when door is closed.
- Strike: ANSI curved lip standard, 4-7/8" x 1-1/4" x 1-1/4" lip to center. Optional strikes, lip lengths and ANSI wrought strike box available.
- Cylinder: Brass, 6-pin, L4 keyway. Other keyways available.
- Keys: Two nickel silver standard.
- Finishes: Available in 626 and other standard architectural finishes.



**Certification/Compliance**

ANSI: Meets A156.2 Series 4000, Grade 1.


*Note: In addition to being available in Corbin regular and IC these locksets are available with a Schlage C keyway, less cylinder with a tailpiece for a Schlage cylinder and prepped for a Best IC cylinder.*

**Trim Designs for CL3300 & CL3600 Series**

**Trim Designs**

**Newport**

Complies with codes requiring lever to return to within 1/2" of door face.



	CL3300	CL3600
*Length	5"	4-1/2"

*Note: In addition to being available in Corbin regular and IC these locksets are available with a Schlage C keyway, less cylinder with a tailpiece for a Schlage cylinder and prepped for a Best IC cylinder. Trim designs shown are only a small sample of the wide variety available. If your needs are not met by what is shown here, please contact us.*

## CORBIN RUSSWIN

### Cylindrical Locks

#### CL3700 Series Light/Medium Duty Lever Locksets

##### Features

- Handing: Non-handed.
- Door Thickness: 1-3/8" to 1-3/4".
- Backset: 2-3/4" standard.  
Optional: 2-3/8".
- Latches: 1/2" bolt projection.
- Auxiliary Latchbolt: Deadlocking latchbolt prevents manipulation when door is closed.
- Strike: T-Strike standard.  
Optional strikes, lip lengths and ANSI wrought strike box available.
- Cylinder: Brass, 6-pin, L4 keyway, 0-bitted standard.
- Keys: Two nickel silver standard.
- Finishes: Available in 626 and other standard architectural finishes.
- Supplied standard with the NZD design. Other designs available.
- Lever handle is free-wheeling in locked position.



##### Certification/Compliance

ANSI: Meets A156.2 Series 4000, Grade 2.

*Note: In addition to being available in Corbin regular and IC these locksets are available with a Schlage C keyway, less cylinder with a tailpiece for a Schlage cylinder and prepped for a Best IC cylinder.*

#### CL3900 Series Standard Duty Key-in-Lever Locksets

##### Features

- Handing: Non-handed.
- Door Thickness: Adjustment (Patent Pending) Standard 1-3/8" and 1-3/4" (factory set for 1-3/4" doors For 2" and 2-1/4" doors, specify door thickness on the order.
- Backset: 2-3/4" standard.  
Optional: 2-3/8", 3-3/4" and 5".
- Latchbolt: 1/2" throw latch with universal "floating" front to fit both flat and beveled doors. 2-1/4" x 1-1/8" square corner front for 2-3/4" backset standard.
- Auxiliary Latchbolt: Deadlocking latchbolt prevents manipulation when door is closed.
- Strike: ANSI curved lip strike standard, 4-7/8" x 1-1/4" x 1-1/4" lip to center.
- Cylinder: Brass, 6-pin, L4 keyway, 0-bitted standard.
- Keys: Two nickel silver standard.
- Finishes: Available in 605, 626 and other standard architectural finishes.
- Supplied standard with the NZD design. Other designs available.
- Lever handle is free-wheeling in locked position.



##### Certification/Compliance

ANSI: Meets A156.2 Series 4000, Grade 2.

U.L./U.L.C.: All locks listed for A Label Single doors. Letter F and U.L. symbol on latch front indicate listing.

*Note: In addition to being available in Corbin regular and IC these locksets are available with a Schlage C keyway, less cylinder with a tailpiece for a Schlage cylinder and prepped for a Best IC cylinder.*

#### CK4200 Series Heavy Duty Cylindrical Knob Locksets

##### Features

- Handing: Field reversible.
- Door Thickness: 1-3/4" to 2" standard.  
Optional door thickness available.
- Backset: 2-3/4" standard.  
Optional: 3-3/4", 5" and 7".
- Front: 2-1/4" x 1-1/8". Accommodates doors beveled 1/8" in 2".  
Optional: flat front.
- Latchbolt: 5/8" throw, with nylon insert.
- Auxiliary Latchbolt: Deadlocking latchbolt prevents manipulation when door is closed.
- Strike: ANSI curved lip standard, 4-7/8 x 1-1/4" x 1-1/4" lip to center.  
Optional strikes, lip lengths and ANSI wrought strikebox available.
- Cylinder: Brass, 6-pin, L4 keyway, 0-bitted standard.
- Keys: Two nickel silver standard.
- Finishes: Available in 626 and other standard architectural finishes.



##### Certification/Compliance


ANSI: Meets A156.2 Series 4000, Grade 1.

##### Trim Designs







###### GRC


Knob: Wrought reinforced

Rose: Wrought reinforced



*Note: Trim designs shown are only a small sample of the wide variety available. If your needs are not met by what is shown here, please contact us.*

Functions OUTSIDE   INSIDE KNOB/LEVER	SERIES/ FUNCTION	TYPE	ANSI NO. SERIES 4000	FUNCTION DESCRIPTION
	CL3310 CL3610 CL3710 CL3910 CK4210	Passage or Closet Both levers always free.	F75	Latchbolt by lever either side.
	CL3320 CL3620 CL3720 CL3920 CK4220	Privacy Bedroom or Bathroom	F76	Latchbolt retracted by lever either side unless outside lever is locked by inside button. Inside lever is always free. Emergency release tool unlocks outside lever.
	CL3351 CL3651 CL3751 CL3951 CK4251	• Entrance or Office	F81/F82	Deadlocking latchbolt by lever either side, except when turn button locks outside lever. Pushing turn button in locks outside lever, requiring use of key outside to unlock. Pushing in and turning button locks outside lever, requiring key at all times. Turning inside lever does not unlock outside lever until button is manually turned to unlocked position. Inside lever always free.
	CL3355 CL3655 CL3755 CL3955 CK4255	• Classroom	F84	Deadlocking latchbolt by lever either side, except when key outside locks outside lever. Outside lever unlocked by key outside. Inside lever always free.
	CL3357 CL3657 CL3957 CK4257	• Storeroom or Closet	F86	Deadlocking latchbolt by key in outside lever or by rotating lever. Inside lever always free
	CL3759	• Barrier-Free Storeroom or Public Restroom	—	Deadlocking latchbolt by lever inside. Key outside unlocks outside lever to retract latchbolt. Lever retracts latchbolt. Key is retained in the unlocked mode. When key is removed, outside lever is locked. Inside lever always free.

 Indicates knob/lever rigid at all times.

 Indicates optional interchangeable core available