



300, 600 and 700 Series Indication Switches

- LBMLCM, LCBDM, LCBM, DBS, LBM, LCMA, LCBMA
- Single-pole, double-throw type (SPDT)
- Ratings: 5 amps @125 or 250 VAC (optional only)

400 Series Indication Switches

- BL, BUL, DPS
- Single-pole, double-throw type (SPDT)
- Ratings: 10 amps @125 or 250 VAC (optional only)

Electrical Ratings for All 310 Strike Solenoids

	VOLTAGE							
	AC			DC				
	12	24	120	6	12	24	48	120
Resistance in OHMS ± 10%	6.2	23.5	500	6.2	23.5	96.0	380	2100
Watts Seated	5.4	5.8	6.3	5.8	6.1	6.0	6.1	6.3
Amps Seated	.45	.24	.06	.97	.51	.25	.13	.06
Amps Inrush	1.33	.69	.16	—	—	—	—	—

Electrical Ratings for 700 Strike Solenoids

	VOLTAGE DC					
	6	12	16	24	48	120
Resistance in OHMS ± 10%	10	41	73	160	640	3700
Watts	3.60	3.48	3.52	3.60	3.60	3.84
Amps	.6	.29	.22	.15	.075	.032

Electrical Ratings for All 600 Strike Solenoids

	VOLTAGE DC					
	6	12	16	24	48	120
Resistance in OHMS ± 10%	10	41	73	165	660	3800
Watts	3.6	3.5	3.5	3.5	3.5	3.5
Amps	.60	.29	.22	.15	.075	.03

Electrical Ratings for All 401 Deadbolt Solenoids

	VOLTAGE DC	
	24V	120V
Watts Inrush	150	150
Watts Seated	10	10
Amps Inrush	6.25	1.30
Amps Seated	.417	.087