



310-2



310-2-3/4



310-2-3/4OB



310-3-1

*NOTE: These products will require relocation of the strike center line when used with mortise locks. Consult HES Customer Support regarding use with the Best 40 series.*

# 310 Series

The industrial grade, **fire-rated solution** for high abuse applications

The 310 series is a 3 hour fire-rated, industrial grade electric strike designed for extreme heavy duty applications. The all stainless steel construction of this device makes it ideal for high abuse applications that would disable other electric strikes.

## 310-2

For a 1/2" or 5/8" throw latchbolt (without deadbolt) on single and pairs of doors

*1/2" keeper standard*

## 310-2-3/4

For a 3/4" throw latchbolt (without deadbolt) on single doors and pairs of doors

*3/4" keeper standard*

## 310-2 3/4OB

For a pair of doors, without a door coordinator, which are equipped with a lock having a 3/4" throw latchbolt (without deadbolt)

*3/4" keeper standard*

## 310-3-1

For a lockset with both a 3/4" throw latchbolt and a 1" throw deadbolt

- Deadbolt must be retracted manually
- Position of block within cavity is adjustable for RH and LH applications

*1" keeper standard*

## Specifications

- UL 10C fire-rated, 3-hour single door (fail secure only)
- UL 10C fire-rated, 3-hour double door (fail secure only)
- CAN4-S104 (ULC-S104) fire door conformant
- UL 1034, burglary-resistant listed
- UL 294 (6th Edition) listed
- ANSI/BHMA A156.31, Grade 1
- New York City accepted
- NFPA-252 fire door conformant
- ASTM-E152 fire door conformant
- RoHS compliant

## Electrical (continuous duty)

- .51 Amps at 12 VDC
- .25 Amps at 24 VDC

## Standard Features

- Tamper-resistant, heavy duty construction
- Constructed entirely of stainless steel for strength and corrosion resistance
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance rating 500,000 cycles
- Horizontally adjustable keeper allows for door and frame misalignment
- 1/2" keeper depth (310-2)
- 3/4" keeper depth (310-2 3/4 and 310-2 3/4OB)
- 1" keeper depth (310-3-1)
- Non-handed
- Fail secure
- Plug-in connector
- Five-year limited warranty

## Optional Features

- Fail safe

**LCBMA** » Latchbolt & Locking Cam Monitor with Auxiliary Switch (all except 310-2-3/4OB)

## Accessories

- 152** » Universal mounting tabs
- 310-2-3** » Strike latch guard (astragal)
- 2001-1** » Wire-in bridge rectifier
- 2001M** » Plug-in bridge rectifier
- 2004M** » ElectroLynx® adapter
- 2005M3** » SMART Pac® III
- 2006M** » Plug-in buzzer

## Finishes

- 630** » Satin stainless steel
- 605** » Bright brass
- 606** » Satin brass
- 612** » Satin bronze
- 613** » Bronze toned
- 629** » Bright stainless steel



CYLINDRICAL  
LOCKSETS



MORTISE  
LOCKS WITH  
DEADBOLTS



MORTISE LOCKS  
WITHOUT  
DEADBOLTS



FIRE RATED



GRADE 1



UL 1034  
BURGLARY  
LISTED

