

Security Safes

“B” rated burglary safe is welded inside a fire resistive safe.

Features

- Class “B” Rated interior safe construction. Door of inner safe will interchange with other Gardall safes with key lock or combination.
- Fire Resistive Exterior Safe—insulated to withstand 1700° for 1 hour.



Z-4820



Z-4220

- Relocking device — if back cover is knocked off of the lock, the independent relock device is activated, preventing bolt withdrawal.
- Boltwork Interior Door — triple boltwork with independent relock device.
- Boltwork Exterior Door — interlocking bolts extend into the safe walls, full length locking bar on hinge side of door to deter forcible entry by removal of hinges.
- Tan or gray.

Lock options

- Mas-Hamilton and electronic pushbutton.

Models Z-1812, Z-1818, Z-2018, Z-3018, Z-3620, Z-4220 and Z-4820

MODEL	OUTSIDE H X W X D	INSIDE* H X W X D	INSIDE CUBIC (INCHES)	APPROX. WEIGHT (LBS.)	STANDARD ADJ. SHELVES
Z-1812	25 x 17-1/4 x 20-1/4	MS — 9-3/4 x 12-1/2 x 9 SS — 7-1/4 x 12-1/2 x 10-3/4	MS — 1096 SS — 974	338	NA
Z-1818	25 x 17-1/4 x 26-1/4	MS — 9-3/4 x 12-1/2 x 15 SS — 7-1/4 x 12-1/2 x 16-3/4	MS — 1828 SS — 1518	410	NA
Z-2018	28 x 22-1/4 x 26-1/4	MS — 12-1/2 x 17 x 15 SS — 7-1/2 x 17-1/2 x 17-1/2	MS — 3188 SS — 2198	568	NA
Z-3018	38 x 22-1/4 x 26-1/4	MS — 12-1/2 x 17 x 15 SS — 17-1/2 x 17-1/2 x 17-1/2	MS — 3188 SS — 5130	690	2
Z-3620	44-3/4 x 25-3/4 x 28-1/4	MS — 12-1/2 x 20-1/4 x 17-1/4 SS — 23-1/4 x 20-1/2 x 18-3/4	MS — 4366 SS — 8937	1035	2
Z-4220	50-3/4 x 25-3/4 x 28-1/4	MS — 12-1/2 x 20-1/4 x 17-1/4 SS — 29-1/4 x 20-1/2 x 18-3/4	MS — 4366 SS — 11243	1140	3
Z-4820	57-1/2 x 25-3/4 x 28-1/4	MS — 12-1/2 x 20-1/4 x 17-1/4 SS — 35-1/4 x 20-1/2 x 18-3/4	MS — 4366 SS — 13550	1225	3

*MS — Money safe

SS — Shelf space above money safe
All dimensions in inches.