

**Burglary Safes**

**U.L. Listed  
Fire Rated  
Burglary  
Safes**

The AMSEC BF™ Series offers a unique design that combines all the security features of a burglary safe and the peace of mind achieved with a fire safe. The industry's first U.L. Listed fire rated burglary safe offers an affordable solution when burglary and fire protection are an essential part of the buying decision! During Underwriters Laboratories' grueling testing procedures, the BF series earned the U.L. Listed Class 350°F, One Hour Fire Label and the Residential Security Container Burglary label.



BF1512

**Features**

- Door, 3-1/2" thick, consisting of 1/2" plate steel with a unique proprietary fire and burglary resistant material.
- Body, 2" thick, consisting of 1/8" outer and inner steel plates creating a single structure enclosing a unique proprietary fire and burglary resistant material.
- Three massive 1" diameter solid steel chrome-plated locking bolts.
- One recessed anchor bolt hole and mounting hardware are provided to securely anchor safe.
- Durable granite textured finish standard. Ivory and onyx finishes are available on a special order basis.
- 3 lock styles are available: standard dial, ESL 10 electronic lock, and Mas-Hamilton electronic lock.

**Models**

BF1512, BF1716, BF2116 and BF3416

**Fire-Rated Burglary Series Safes**

| MODEL   | INSIDE<br>H X W X D  | OUTSIDE**<br>H X W X D | DOOR OPENING<br>H X W | CUBIC INCH<br>CAPACITY | WEIGHT<br>LBS. | INTERIOR<br>SHELVES |
|---------|----------------------|------------------------|-----------------------|------------------------|----------------|---------------------|
| BF1512  | 15 x 12 x 13         | 19 x 16 x 18-3/4       | 15 x 12               | 2,340                  | 280            | 1                   |
| BF1716  | 17 x 16-1/2 x 16     | 21 x 20-1/2 x 21-3/4   | 17 x 16-1/2           | 4,488                  | 400            | 1                   |
| BF2116  | 21 x 16-1/2 x 14-1/2 | 25 x 20-1/2 x 20-1/4   | 21 x 16-1/2           | 5,024                  | 440            | 1                   |
| BF3416* | 34 x 16-1/2 x 16     | 38 x 20-1/2 x 21-3/4   | 34 x 16-1/2           | 8,976                  | 640            | 2                   |

\* U.L. Class 350°F, 30 minute fire label.

\*\* Add 2" to outside depth for handle, dial and hinge projection.  
All dimensions in inches.