

Wall Safes



WS1014

WS1514

Each Wall Safe is designed for easy installation between 6" wall studs with pre-drilled anchor holes and a built in flange eliminating unnecessary replastering. Models available are WS1014, WS1514, WS1214 and WFS1310 (fire-rated wall safe).



WS1214

WFS1310

Heavy Duty WS1214 Features

- 3/4 inch thick solid steel door, recessed for flush mounting.
- Heavy duty "B" rate fully welded body construction with flange.
- A handle activated locking mechanism consisting of five 3/4 inch diameter chrome steel locking bolts.
- One removable shelf.
- Attractive black finish with brass plated dial and gold emblem.

WS1014/WS1514 Features

- Flat dial allows flush mounted installation.
- 3/16 inch thick solid steel door with dead bar.
- Attractive parchment textured finish.
- Continuous non-removable hinge.
- Flange covers rough opening.

WFS1310 Features

- 350°F, 1 hour JIS fire rating.
- Side locking boltwork mechanism incorporating a 5/8" x 1-1/4" rectangular steel locking bolt.
- Two 5/8" x 1-1/4" rectangular steel deadbolts preventing door removal during forced entry.
- 3 wheel changeable combination lock with separate key lock.
- Flange covers rough opening.

Options

- WS1014, WS1214 and WS1514 can be ordered with the Mas-Hamilton 50LP (low profile) or the LaGard 33E electronic locks. Both must be ordered with a Slam Bolt rather than a standard bolt.
- The WFS1310 is not available with an electronic lock.

Wall Safes

MODEL	INSIDE H X W X D	OUTSIDE H X W X D	DOOR OPENING	CUBIC INCH CAPACITY	WEIGHT LBS.	INTERIOR SHELVES
WS1014	10 x 13-3/4 x 3-1/2	12-1/4 x 15-3/4 x 4	9-5/8 x 12-3/4	481	26	1
WS1514	15 x 14 x 3-1/2	16-1/2 x 15-1/2 x 4	14 x 13-1/4	688	24	2
WS1214	12 x 13-1/2 x 5-1/2	12-5/8 x 14-1/8 x 10	10-3/4 x 11-1/8	891	75	2
WFS1310	13 x 10 x 11	17 x 13-1/2 x 15-1/2	11-1/2 x 8-1/4	1,430	80	1

All dimensions in inches.