

**Fire Rated Composite Safes**

**Amvault TL-30 and TL-15 Fire Rated Composite Safes**

Besides withstanding the most concentrated attacks by sophisticated burglars, each Amvault safe offers a 2 Hour, 350° factory fire test certification, ensuring the protection of the vault's contents against intense fires.

**Models**

CE1814, CF1814, CE2518, CF2518. Other models are available on a special order basis.

**Door Features**

- Overall thickness of 5-3/4" and is constructed with a 2-3/4" defense barrier of outer and inner steel plates enclosing a solid steel defense barrier and a unique, high density fire and burglary resistant composite material.
- The Amvault TL-30 offers a massive solid steel hard plate covering the entire door. Contemporary style hinges with adjustable self lubricating ball bearings, insure a lifetime of use.



CE2518

**Body Features**

- 3-1/2" thick body constructed of inner and outer steel plates enclosing a solid steel defense barrier and a high density proprietary composite material.
- A reinforced drill resistant, door frame protects the door and each individual bolt chamber from severe side attacks.

**Standard Locking Mechanism**

- Entire boltwork mechanism is also protected by a spring operated boltwork detent system. Bolts stay in the retracted position when the door is opened and automatically engages when the door is closed.

**U.L. Label — Burglary Classification TL-15**

Signifies a combination-locked safe designed to offer a limited degree of protection against attack by common mechanical and electrical hand tools and any combination of these means.

- Specify with prefix CE

**U.L. Label —Burglary Classification TL-30**

Signifies a combination-locked safe designed to offer a moderate degree of protection against attack by common mechanical and electrical hand tools and any combination of these means.

- Specify with prefix CF

**Options**

- All Composite Safes can be ordered with the Mas-Hamilton 50LP (low profile) or the LaGard 33E electronic locks. Both must be ordered with a Slam Bolt rather than a standard bolt.

**Amvault TL-15 and TL-30 Safes**

MODEL*	INSIDE H X W X D	OUTSIDE** H X W X D	CUBIC FEET	WEIGHT TL-15/TL-30	INTERIOR SHELVES	A	B	C
1814	18 x 14 x 12	25 x 21 x 21-1/2	1.8	816/836	1	14	36	39-1/2
2518	25 x 18 x 16	32 x 25 x 25-1/2	4.2	1,236/1,275	1	18	44	47-1/2
3524†	35 x 24 x 20	42 x 31 x 29-1/2	9.7	1,955/2,020	2	24	56	57-1/2
5524†	55 x 24 x 20	62 x 31 x 29-1/2	15.3	2,682/2,787	3	24	56	57-1/2

\* Add prefix CE for TL-15 and CF for TL-30.

\*\* Add 2" to outside depth for handle, dial and hinge projection.

† Special order only.

All dimensions in inches.