

U.L. Listed 2 Hour Fire and Impact Safes

Introducing AMSEC's new U.L. listed Class 350° Two Hour Fire and Impact Safes.

Features

- U.L. Listed Class 350° 2 hour fire and impact rating.
- Safes withstand fires of up to 1850° for 2 hours and a 30 foot drop – equivalent to falling through a three story burning building.
- Increased barriers for burglary protection. Impressive 3-1/2" thick recessed door with 5/8" thick front for excellent pry resistance.
- Handle activated locking mechanism with 7/8" diameter solid steel chrome plated locking bolts offering smooth operation.



UL1511 with optional electronic lock



UL2018

- Internal anchor bolt hole with hardware.
- Auxiliary spring-loaded relock device activated by severe attack.
- Heavy duty steel hinges provide additional security and smooth operation.
- For your convenience, rubber feet are standard on models UL1511 – 1812XD.
- Heavy duty rolling casters on UL2018 and up.
- Attractively accented with a brass-plated dial, brown powder coated handle, decorative emblems and plush velour interior.
- Available in durable sandstone (beige) or granite (grey) textured finish.

Options

- Mas-Hamilton or AMSEC ESL10 electronic lock (see page for 7 for lock options).

U.L. Safes

MODEL	INSIDE H X W X D	OUTSIDE H X W X D	DOOR OPENING	CUBIC INCH CAPACITY	WEIGHT LBS.	INTERIOR SHELVES
UL(*)1511	15 x 11-1/2 x 12	21-1/2 x 17 x 18	15 x 11-1/2	2,070	215	1
UL(*)1812	18-1/2 x 12-1/2 x 12	25 x 18 x 18	18-1/2 x 12-1/2	2,775	260	1
UL(*)1812XD	18-1/2 x 12-1/2 x 17	25 x 18 x 23	18-1/2 x 12-1/2	3,931	310	1
UL(*)2018	20 x 18 x 18	30-1/4 x 25-1/2 x 25-1/2	20 x 18	6,480	480	2
UL(*)2818	28 x 18 x 18	38-1/4 x 25-1/2 x 25-1/2	28 x 18	9,072	620	2

(* Substitute (S) for Sandstone or (G) for granite finish.

* Add 2" to outside depth for handle, dial and hinge projection. Outside height includes rubber feet on models UL1511 – 1812XD and rolling casters on models UL2018 – UL3918.
All dimensions in inches.