

PRODUCT FEATURES

- Single gang, stainless steel plate with low voltage mounting ring
- 12 key illuminated 3x4 keypad
- True 10-digit operation (10 digits plus * and # keys)
- 99 user code capability
- Easy programming from the keypad
- Passage mode and Lockout mode
- Configurable audible keystroke echo
- Red, green and yellow LEDs for status and programming feedback
- · Fail secure or fail safe-capable
- Easy to install with simple hand tools
- Accepts 12V or 24 VAC or DC current
- 5A SPDT timed, control relay output
- · Request to exit (REX) input
- MagnaCare® lifetime replacement, no fault warranty

PRODUCT OPTIONS

- · Weather-resistant cover (WCC)
- Weather-resistant backbox (WBB)

SPECIFICATIONS

Dimensions:

2-3/4"W x 4-1/2"H x 5/32"D

Electrical:

12/24 VDC: 70 mA

Maximum 30 VDC or 300 VAC switched voltage

Operating Temperature:

-10 to +140F [-23 to +60C] Primarily for indoor applications

Shipping Weight:

1lb [0.45kg]

Finishes:

US32B/630 - Satin Stainless Steel

Need an Outdoor Solution?



WCC and WBB allow DK-12 keypad to be mounted in outdoor locations not directly exposed to rain or snow




ASSA ABLOY, the global leader in door opening solutions

DK-12Digital Keypad System

All-in-One Keypad System for Single-Door Traffic Control

The DK-12 standalone keypad and controller is ideal for lower security requirements such as traffic control. Easy to install and easy to program, the one-piece DK-12 supports 99 user codes, including Passage mode and Lockout mode.







67