

# Rockwood LP7901

## GeoMetek Locking Pull

Experience a safer  
and more open world



### BENEFITS:

- Cylinder and thumbturn location eliminates physical strain when locking and unlocking.
- Glass door applications secure the opening and allow for more natural light.
- Bolt concealed inside pull provides a clean, streamlined look.
- Simple door preparation allows for faster installation.
- Suites with popular Rockwood door pulls, CORBIN RUSSWIN and SARGENT lever handles, McKINNEY hinges, creating a continuum of design.
- Offers flexibility in custom sizes for a variety of applications.

### SPECIFICATIONS:

#### FEATURES:

- Key operated from outside; turn piece on inside.
- Cylinder options: Rim Cylinder, Small format interchangeable core housing: 7-pin (SFIC) less core and key (Standard), Small format interchangeable core housing w/plastic construction core: 7-pin (SFIC), Customer Supplied Cylinder, Dummy Cylinder, or Privacy Function: keyless locking function.
- Door types:  $\frac{3}{8}$ " -  $\frac{7}{8}$ " thick glass,  $1\frac{3}{8}$ " -  $2\frac{1}{2}$ " thick aluminum, hollow metal or wood doors.
- Multiple locking options: floor, head or both.
- Bolt location: 2" from face of door to centerline of bolt.
- Bolt has  $\frac{13}{16}$ " travel with fine adjustment.
- ADA Thumbturn comes standard with this product.

#### APPLICATIONS:

- Store fronts, glass houses, slider doors, interior offices.

### AVAILABLE FINISHES:

- 10BE/613E
- US32/629
- US32D/630
- US32MS
- US32DMS
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- Stock Powder Coats

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
www.rockwoodmfg.com  
1 800 458 2424

Copyright © 2019-2022, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.